





WATER BASED EPOXY PARTS A&B

HIGH GLOSS SURFACE SEALER

WATER BASED EPOXY IS A SUPER HIGH GLOSS EPOXY SURFACE SEALER FOR ALL INTERIOR LATERAL CONCRETE SURFACES, OVERLAYS, METALLICS, COUNTER TOPS, CONCRETE FLOORS & CHIP BROADCAST SYSTEMS. LOW VOC.

PRODUCT HIGHLIGHTS

- High gloss clear finish, with a clear wet appearance.
- Low Odor
- Resistant: Common chemicals, solvent resistant
- Excellent abrasion resistance
- VOC Compliant

Solids Content: 60%

- Available in 1.25gallon, 2.5gallon and 5gallon kits
- Mixing Ratio: 4 : 1 (4 Parts A to 1 Part B)

QUICK LOOK: PART A

Ratio: 4 : 1 by volume

Toxicity: Harmful if swallowed VOC's: Low Flammability: Non-Flammable Composition: Color: Odor: Coverage: 400-500sq.ft. per gallon @ 3-4mLs *Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.

FOR MORE INFORMATION. PLEASE SEE SDS.



USES

Effective on many interior applications where a low odor, abrasion resistant coating is required.

SPECS

- 400-500 sq. ft. per gallon
- 2-3 Mils Wet
- Pot Life = 1.5 hrs +
- Tack Free for 2 3 hours
- Re Coat = 4 20 hours
- Foot Traffic = 24 hours
- Vehicle Traffic = 72 hours

QUICK LOOK: PART B

Solids Content: 60% Ratio: 4 : 1 by volume Toxicity: Harmful if swallowed VOC's: Low Flammability: Non-Flammable Composition: Color: Odor: Coverage: 400-500sq.ft. per gallon @ 3-4mLs *Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.

FOR MORE INFORMATION. PLEASE SEE SDS.



Manufactured In The USA By

*Product warranty for one year from date of manufacture For more information on Water Based Epoxy and all products manufactured by Gladiator Coatings please visit GLADIATOR our website: www.gladiatorcoatings.com

WATER BASED EPOXY PARTS A & B

HOW TO USE:

Add four parts by volume of Part A to one part of Part B and blend thoroughly until completly mixed. May be used immediately. Apply by brush. Dry to touch in 2-3 hours. A second coat can be applied in 3-4 hours. Use detergent and water for clean up.

POT LIFE:

The pot life of this product is one hour. Shelf Life is up to one year from manufacture date in its original, unopened container stored at room temperature.

PRECAUTIONARY STATEMENT:

PART A: Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Dispose of contents/ container according to local, state and federal regulations.

PART B: Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Dispose of contents/ container according to local, state and federal regulations.

FIRST AID:

EYES: Flush thoroughly with water, lifting both eyelids. Get Medical Help. SKIN: Wash with soap and water. Remove and launder contaminated clothing before reuse. If irritation develops, Get Medical Help. INGESTION: Do not induce vomiting. Get Immediate Medical Help. INHALATION: Remove to fresh air immediately. If breathing difficulty continues, administer oxygen and Get Medical Help.

IN CASE OF FIRE:

This product is not flammable.

FOR PROFESSIONAL USE ONLY

FOR EMERGENCY HELP 24 Hours a Day contact: INFOTRAC at 1-800-535-5053

GLADIATOR